

APIS

- Sending Emails**
 - Send campaign email [POST](#)
 - Broadcast campaign to a list [POST](#)
- User Journeys**
 - Add a new user to the journey [POST](#)
 - Abort the journey for a user [POST](#)
- Dynamic form**
 - Send email with dynamic form [POST](#)
- Repeatable Block**
 - Send email with repeatable block [POST](#)
- Contact Management**
 - Add contact to a list [POST](#)
 - Bulk add contact to a list [POST](#)
 - Get all contact lists [GET](#)
 - Suppress/unsubscribe a contact [POST](#)
 - Update Subscription [POST](#)
 - Get contact details [GET](#)
 - Resubscribe contact [POST](#)
 - Remove contact from a list [POST](#)
 - Archive an existing contact [DELETE](#)
- Custom Events**
 - Add Event [POST](#)
- Campaign Data**
 - API to get list of campaigns [GET](#)
 - API to get summary data for all c... [POST](#)
 - API to get summary data for an in... [POST](#)
- Templates**
 - Get All Templates [GET](#)

Add Event

POST <https://api.mailmodo.com/api/v1/addEvent>

The add event API provides you the ability to add custom events of a contact using email as an identifier

Adding events requires a POST request with a JSON payload specifying the email and the event information.

Please note that we only accept event names with type as string and event properties with types as either string, number, or boolean
One event can be sent per API call.

i You can send us old events using the optional **ts** attribute which accepts the time of the occurrence of the event as a UNIX timestamp. Ex: 1653304684

Auth

mmApiKey : 123

Parameters

Content-Type* : application/json

Body

```

1 {
2   "email": "string",
3   "event_name": "string",
4   "ts": 0,
5   "event_properties": {
6     "testStringProperty1": "string",
7     "testIntegerProperty1": 0,
8     "testBooleanProperty1": true
9   }
10 }

```

Send API Request

Request Sample: Shell / cURL

```

curl --request POST \
--url https://api.mailmodo.com/api/v1/addEvent \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--header 'mmApiKey: ' \
--data '{
  "email": "string",
  "event_name": "string",
  "ts": 0,
  "event_properties": {
    "testStringProperty1": "string",
    "testIntegerProperty1": 0,
    "testBooleanProperty1": true
  }
}'

```

Request

> Security: API Key

Headers

Content-Type string **required**
application/json
Default: application/json

mmApiKey string **required**
Please input your API key available at <https://manage.mailmodo.com/app/settings/apokey>

Body application/json

email string **required**
Email address of the contact

Response Example

```

1 {
2   "success": true,
3   "ref": "string"
4 }

```

ts number
Timestamp of the occurrence of the event formatted as UNIX epoch in seconds. Ex: 1653303900. It'll default to the current timestamp if not sent.
Default: 0

event_properties object
Properties if any associated with the event. Passed as key : value pairs

- testStringProperty1** string
>= 1 characters
- testIntegerProperty1** number
- testBooleanProperty1** boolean

Responses 200

Body application/json

responses / 200

success boolean **required**
Status of the event addition

ref string **required**
Reference ID for the event added
>= 1 characters



Registered Address (US)
Mailmodo Technologies Inc.
16192, Coastal Highway
Lewes, Delaware, 19958
United States

Registered Address (India)
Mailmodo Technologies Pvt Ltd
Hanto Rebel Building, 3rd Floor
2751/492, 2nd Sector
HSR Layout Bangalore
Karnataka, India - 560102

enquiries@mailmodo.com



[Help](#)

[Features](#)

[Marketing Partner](#)

[Affiliate Program](#)

[GDPR Compliance](#)

[Book a Demo](#)

[Contact Us](#)

[Security](#)

Product

[Email Marketing](#)

[Customer Engagement](#)

[AMP Emails](#)

[Surveys](#)

[Shopify Email Marketing](#)

[Email Deliverability](#)

[Email Template Builder](#)

[Send Transactional Email](#)

[Bulk Email Service](#)

[Email Automation](#)

[Newsletter Software](#)

[Email Masterclass](#)

[Template Suggestion](#)

Resources

[AMP Email Guide](#)

[Email Marketing 101](#)

[Email Templates](#)

[Email Flows](#)

[Email Subject Lines](#)

[Email Checklist](#)

[Email Stash](#)

[AI Subject Line Generator](#)

[Use cases](#)

[Case Studies](#)

[Guides](#)

[Ebooks](#)

[Podcasts](#)

[Videos](#)

[Newsletters](#)

[Marketing Tools](#)

[Marketing Experts Network](#)

How We Compare

[Mailjet vs Mailmodo](#)

[Brevo vs Mailmodo](#)

[Omnisend vs Mailmodo](#)

[Zoho Campaigns vs Mailmodo](#)

[Moosend vs Mailmodo](#)

[SendPulse vs Mailmodo](#)

[Drip vs Mailmodo](#)

[GetResponse vs Mailmodo](#)

[AWeber vs Mailmodo](#)

[Campaign Monitor vs Mailmodo](#)

[Mailgun vs Mailmodo](#)

[ConvertKit vs Mailmodo](#)

© 2024 mailmodo

[Terms of Service](#)

[Privacy Policy](#)

[Cookie Policy](#)

Mailmodo API for Transactional Email

Getting Started with Mailmodo API

Use cases

APIS

- Sending Emails**
 - Send campaign email [POST](#)
 - Broadcast campaign to a list [POST](#)
- User Journeys**
 - Add a new user to the journey. [POST](#)
 - Abort the journey for a user [POST](#)
- Dynamic form**
 - Send email with dynamic form [POST](#)
- Repeatable Block**
 - Send email with repeatable block [POST](#)
- Contact Management**
 - Add contact to a list [POST](#)
 - Bulk add contact to a list [POST](#)
 - Get all contact lists [GET](#)
 - Suppress/unsubscribe a contact [POST](#)
 - Update Subscription [POST](#)
 - Get contact details [GET](#)
 - Resubscribe contact [POST](#)
 - Remove contact from a list [POST](#)
 - Archive an existing contact [DELETE](#)
- Custom Events**
 - Add Event [POST](#)
- Campaign Data**
 - API to get list of campaigns [GET](#)
 - API to get summary data for all c... [POST](#)
 - API to get summary data for an in... [POST](#)
- Templates**
 - Get All Templates [GET](#)

Add contact to a list

POST <https://api.mailmodo.com/api/v1/addToList>

Add contacts to a list without sending an email. The list will be available at Mailmodo portal so that you can send them ad-hoc emails.

Numbers, Booleans, Strings and Dates (in UNIX or ISO 8601) are supported inside the data object

Parameters

Content-Type* : string
mmApiKey* : string

Body

```

1  {
2    "email": "string",
3    "data": {
4      "first_name": "string",
5      "last_name": "string",
6      "name": "string",
7      "gender": "string",

```

Send API Request

Request Sample: Shell / cURL

```

curl --request POST \
  --url https://api.mailmodo.com/api/v1/addToList \
  --header 'Accept: application/json, application/xml' \
  --header 'Content-Type: application/json' \
  --header 'mmApiKey: ' \
  --data '{
    "email": "string",
    "data": {
      "first_name": "string",
      "last_name": "string",
      "name": "string",
      "gender": "string",
      "age": 0,
      "birthday": null,
      "phone": "string",
      "address1": "string",
      "address2": "string",
      "city": "string".

```

Response Example

```

1  {
2    "success": true,
3    "message": "string"
4  }

```

Request

Headers

Content-Type string **required**
application/json

mmApiKey string **required**
Please input your API key available at <https://manage.mailmodo.com/app/settings/apikey>

Body

Post the necessary fields for the API to create a new user.

email string **required**
Email Address of the user

data object

- first_name** string
First name of the user
- last_name** string
Last name of the user
- name** string
Full name of the user
- gender** string
Gender of the user
- age** integer
Age of the user in numbers
- birthday**
Birthdate of the user in ISO format (Can also sent as UNIX timestamp)
- phone** string
Primary phone number of the user
- address1** string
Line 1 of the address of the user
- address2** string

Line 2 of the address of the user

city string

Name of the city (or district, village or town) of the user

state string

State, region or province of the user

country string

Country of the user

postal_code string

PIN/ZIP Code of the user

designation string

Designation of the user, usually related to their position at a specific company. Example: "VP of Engineering"

company string

Company of the user

industry string

Industry of the user

description string

Description of the user

anniversary_date

Anniversary date of the user in ISO format (Can also sent as UNIX timestamp)

created_at

The date and time, the user was originally created in ISO 8601 or UNIX format

last_click

The date and time of the user's last mail open in ISO 8601 or UNIX format

last_open

The date and time of the user's last mail click in ISO 8601 or UNIX format

listName string required

Name of the list to which the user should be added

timezone string

Timezone of the user in [region format](#)

Responses

200

OK

Body

application/json ▾

responses / 200

success boolean required

message string required

Mailmodo API for Transactional Email

Getting Started with Mailmodo API

Use cases

APIS

- Sending Emails**
 - Send campaign email [POST](#)
 - Broadcast campaign to a list [POST](#)
- User Journeys**
 - Add a new user to the journey. [POST](#)
 - Abort the journey for a user [POST](#)
- Dynamic form**
 - Send email with dynamic form [POST](#)
- Repeatable Block**
 - Send email with repeatable block [POST](#)
- Contact Management**
 - Add contact to a list [POST](#)
 - Bulk add contact to a list [POST](#)
 - Get all contact lists [GET](#)
 - Suppress/unsubscribe a contact [POST](#)
 - Update Subscription [POST](#)
 - Get contact details [GET](#)
 - Resubscribe contact [POST](#)
 - Remove contact from a list [POST](#)
 - Archive an existing contact [DELETE](#)
- Custom Events**
 - Add Event [POST](#)
- Campaign Data**
 - API to get list of campaigns [GET](#)
 - API to get summary data for all c... [POST](#)
 - API to get summary data for an in... [POST](#)
- Templates**
 - Get All Templates [GET](#)

Send campaign email

POST .../api.mailmodo.com/api/v1/triggerCampaign/{campaign-id}

The send campaign API allows the user to trigger campaigns with personalization parameter added to the email template. To call this API, you will need the campaign id.

- Auth
 - mmApiKey : 123
- Parameters
 - campaign-id* : string
 - Content-Type* : string
- Body

Request

> Security: API Key

Path Parameters

campaign-id string **required**

Headers

Content-Type string **required**
application/json

mmApiKey string **required**
Please input your API key available at <https://manage.mailmodo.com/app/settings/apikey>

Body application/json

The send campaign API provides two data blocks for sending personalization parameters. These blocks are data and campaign data. Given below is the difference between the two.

- email** string **required**
Provide email address of the contact to whom you want to send email
- subject** string
Send this value if you want to override the default subject line provided at the time of creating the campaign.
- replyTo** string
Send this value if you want to override the default replyTo provided at the time of creating the campaign.

```

1 {
2   "email": "string",
3   "subject": "string",
4   "replyTo": "string",
5   "fromName": "string",
6   "data": {
7     "first_name": "string"

```

Send API Request

Request Sample: Shell / cURL

```

curl --request POST \
  --url https://api.mailmodo.com/api/v1/triggerCampaign/campaign-id \
  --header 'Accept: application/json' \
  --header 'Content-Type: application/json' \
  --header 'mmApiKey: ' \
  --data '{
    "email": "string",
    "subject": "string",
    "replyTo": "string",
    "fromName": "string",
    "data": {
      "first_name": "string"
    },
    "campaign_data": {
      "transient_variable": "string"
    },
    "addToList": "string"
  }'

```

Response Example

```

1 {
2   "success": true,
3   "message": "Email scheduled successfully",
4   "ref": "be2bab1a-e0a6-419c-8fe0-1d3557c2af63"
5 }

```

— **fromName** string

Send this value if you want to override the default fromName provided at the time of creating the campaign.

∨ **data** object

Personalization parameters sent inside the "data" block will be added / update as user attributed against the contact profile.

— **first_name** string

∨ **campaign_data** object

Personalization parameters sent inside the "campaign data" block will not be added / update against the contact profile i.e. they works as transient variables.

— **transient_variable** string

— **addToList** string

Responses 200

OK

Body application/json ∨

responses / 200

— **success** boolean required

— **message** string required

>= 1 characters

— **listId** string

ID of the list created or updated in the API call.



Registered Address (US)

Mailmodo Technologies Inc.
16192, Coastal Highway
Lewes, Delaware, 19958
United States

Registered Address (India)

Mailmodo Technologies Pvt Ltd
Hanto Rebel Building, 3rd Floor
2751/492, 2nd Sector
HSR Layout Bangalore
Karnataka, India - 560102

enquiries@mailmodo.com