

Zepcam T2+ Bodycam Technical specifications

Specifications

Main

Functionalities Video resolution Video format Photo format Photo capture Pre event recording Location

Scene tagging Audio Storage

Video & optics

Sensor video Lens Night vision Light sensitivity w/o IR Infra Red lights

Notifications

Visual

Audio Stealth mode

Battery

Type Charging time Recording time Standby time Charging

Other

IP Class Certification Weight Dimensions Wi-Fi Security Data offload User management Video management Firmware & settings update Mounts

Available Software

Zepcam manager

Zepcam Connect

Integration

Functionality

Recording of video, audio, photo, GPS 1920x1080 - 30 FPS, 1280x720 - 30 FPS, 840x480 - 30 FPS MP4, H.264 Max. 16 MP, JPG Capture photos while video recording or standalone 60s @ 848*480; 60s @ 1280*720; 60s @ 1920*1080 GPS during recording - In-device GPS capture. Not dependent on smartphone GPS connection Yes, including photo shot AAC(LC) 128kb/s, mono ,48khz Storage 64GB (T2-BC2P)

4 MP CMOS 140 degrees wide angle lens, low distortion Low light image sensor 0.5 lux Auto IR mode for dark environments

LEDS for indication of standby, recording, charging LEDS have auto dim. Less bright in low light conditions Audio notification for start / stop recording, disc full, low battery level Disable audio signals and Led indications for stealth operations Selectable setting Built-in vibration notification functionality

Built-in 3200 mAh Lithium-Ion battery 3.5 hours from empty to 80% (fast charge) 11.5 hours (840x480p - 30 FPS), 10.0 hours (1280x720p - 30 FPS), 9.0 hours (1920x1080p - 30 FPS) 11.8 hours (840x480p - 30 FPS), 10.6 hours (1280x720p - 30 FPS), 9.6 hours (1920x1080p - 30 FPS) Zepcam docking station, Single dock with USB charger

IP 65 (rain & dust proof) CE: EMC-directive 2014/30/EU; 2014/53/EU; performed under Dutch Accreditation council 115 gram (without mount) 72x56x24mm (WxHxD) Disabled feature AES 256 bit encryption Via Single dock or Zepcam Docking Station Use Zepcam Manager to manage users, user rights, connect user ID to Camera ID etc. Zepcam Manager or an integrated 3rd party video management system Via Zepcam Manager and Zepcam Connect software Clip mount, 360 degrees rotatable, Peter Jones mount support Option for tripod mount 1/4"-20

Web-Based based software with advanced functionalities Storage on server or cloud T2+ Bodycam placed in Zepcam Docking Station

PC software with basic functionalities Storage on local PC or upload to Zepcam Manager T2+ Bodycam placed in Single Dock

3rd party integration possible with Video Management Systems Milestone, Onvif & Zepcam API.



Zepcam T2+ Bodycam

Technical specifications

T2+ Bodycam Single dock for PC connection USB wallplug charger USB Cable Clip Mount Quick start manual



1 Charging indicator

- (2) Record indicator
- (Red recording / Green standby) (3) Light sensor
- 3 Light sensor
- 4 Infrared light
- 5 Wide angle lens (140 degrees)
- 6 Microphone
- Photo button
- 8 Power/Recording button Press and hold for about 3 to turn on or off Press again to start recording Hold 2 seconds to stop recording
- Oock connector



INTEGRATED SOLUTION: EASY, SECURE AND SCALABLE









Capture video Compact, robust and easy to use bodycams **Dock and upload** Docking station for data exchange and fast recharge Store and manage on the Zepcam cloud or own server

View and manage Zepcam software or 3rd party video management systems